GOMA
RUGGED SOLUTIONS



XRS 2U S8 SOLO Series

EXTREME RUGGED
EDGE SERVERS

www.gomarugged.com

XRS 2U S8 SOLO Series

Extreme Rugged Edge Servers

www.gomarugged.com

The **XRS Series** is a family of Extreme Rugged Servers optimized for Edge applications, where they offer superior robustness and high-performance computing technology.

The **XRS 2U S8 SOLO** offers rugged performance with a single 5th/4th Gen Intel® Xeon® Scalable Processor, featuring advanced security, PCIe 4.0/5.0 support, and AI acceleration. It is an ideal solution for cost-sensitive, power-constrained, and moderate workload environments, providing robust computing for demanding Edge applications without the complexity and overhead of dual processors. The integrated IPMI services enhance Edge operations by supporting monitoring, control, and management functions, sending alarm notifications in case of critical events.
This series features a 2U milled aluminium chassis providing unmatched resistance and torsional strength essential for Edge computing sites, which often face extreme operational demands. It offers configurations with depths of 400mm or 475mm for standard or round MIL-grade I/O connectors, respectively, catering to the specific needs of Edge infrastructure. Capable of accommodating up to five full-length low profile PCIe boards and designed for high-density storage with the capacity for up to six removable SSDs, the **XRS 2U S8 SOLO Series** is robust and versatile. It also includes air filters and protective double-door front panel with optional door-less variants, ensuring secure and reliable operation.

Qualified according to MIL-STD-810G for temperature, shocks, and vibrations, and conforming to MIL-STD-461G for EMI/EMC, the **XRS Series** Extreme Rugged Servers are robustly built to meet the stringent requirements of Edge computing environments.

- **High Performance Single 5th / 4th Gen Intel® Xeon® Scalable Processors Platform**
- **IPMI Based Management**
- **Extreme Rugged Aluminum Chassis**
- **Up to 6x 2.5” SSD**
- **Optional round MIL connectors**
- **MIL Grade Qualifications**



Technical Specifications

System	
CPU	5th Gen Intel® Xeon® / 4th Gen Intel® Xeon® Scalable Processors, Single Socket LGA-4677 (Socket E) supported, CPU TDP Up to 270W
Memory	Up to 2TB ECC RDIMM, DDR5-4800MT/s in 8 DIMM slots
Chipset	Intel® C741
Network Connectivity	1x Dedicated IPMI LAN port 2x 10GbE with RJ45 connectors
USB	2x USB 2.0 ports (2 rear) 4x USB 3.2 Gen1 ports (2 rear; 1 via header; 1 type A)
Storage	Internal: 2x M.2 NVMe; M-Key, 2280/22110 2x SATA Disk on Module Removable: Up to 3x 2.5" SAS SSD or Up to 6x U.2 NVMe SSD or Up to 6x 2.5" SATA SSD
TPM	TPM Header
I/O connectors	1x BMC LAN, 2x USB 3.2, 2x USB 2.0, 2x 10GbE, 1x VGA (available on the rear panel)
Expansion slots	3x PCIe 5.0 x8, 2x PCIe 5.0 x16 low profile slots
Operative Systems	Windows® 11 IoT Enterprise; Windows® 10 IoT Enterprise LTSC; Windows® Server 2022; Windows® Server 2019; RHEL 8.5 64bit; Ubuntu 20.04.6 LTS 64bit; CentOS 8.5 64bit
IPMI	IPMI2.0, SPM, Watchdog; SNMP and e-mail alarms and notifications
Remote Monitoring	Monitoring, control and management functions (fan speed, temperature, voltage, redundant power failure, power consumption, disk health, raid health, and memory health)
Power Section	
Power Input	AC or DC input, redundant PSU. Optional EMC Filter and MIL D38999 connector with single power supplies.
Mechanical Features	
Dimensions (W x D x H)	Width 483mm Depth 400mm - standard I/O ports and industrial power input Depth 475mm - standard I/O ports and MIL grade power input Depth 475mm - MIL grade connectors on I/O ports and power input Height 88mm - 2U rack
Material	Milled Aluminum chassis with surface passivation treatment; AISI316L Stainless steel rear panel.
Weight	<= 8,2 Kg (depending on configuration)
Colour	Black / RAL 9005 - Powder Coating
Mounting	2U 19" rackmount chassis with bridge handles
Front Panel	IP30 double-door front panel with air filters. Optional door-less front panel. Power ON with led; 1 x USB 3.0; Remote Battery Holder.
Rear Panel	Standard connectors. Optional D38999 MIL type connectors for Power Input. Optional D38999 MIL type connectors for Power Input and I/O.
Fan Unit	Removable 6x 40mm fans
Environmental Features	
Operating Temperature	Standard: -5°C to +55°C according to MIL-STD-810G Change 1 (501.6 & 502.6) Extended: -20°C to +60°C (depending on configuration)
Storage Temperature	-40°C to +71°C according to MIL-STD-810G Change 1 (501.6 & 502.6)
Humidity	5% to 95% non-condensed according to MIL-STD-810G Change 1 (506.7 Procedure II)
Fungus	Conformal coating on request
Shock	40g, 11ms functional shock on each direction, according to MIL-STD-810G Change 1 (516.7 Procedure I)
Vibrations	Functional : MIL-STD-810G Change 1 (514.7, Category 20 Procedure I - Wheeled vehicle) Transportation MIL-STD-810G Change 1 (514.7, Category 7 Procedure I - General exposure)
EMC / Electromagnetic Compatibility	According to MIL-STD-461G with EMI Filter and MIL type connectors on power input

GOMA
RUGGED SOLUTIONS

Strada Antica di Collegno, 225
10146 Torino - Italia
Tel. +39 011.7725024

www.gomarugged.com

KEEP IN TOUCH

All trademarks are the property of their respective owners
GOMA ELETTRONICA SpA • XRS2US8SOLO0924
Designed by GOMA ELETTRONICA SpA